

SECTION 1. IDENTIFICATION

Product Identifier	PROPANE (Odorized / Non-odorized)
Other Means of Identification	Liquefied Petroleum Gas
Product Family	Natural Gas Liquids
Recommended Use Restrictions on Use	Fuel for heating, cooking, automobiles, welding/cutting, refrigeration, aerosol propellant. Not recommended for uses other than those listed, or for non-industrial purposes.
Manufacturer/Supplier Identifier	Keyera and Affiliates Suite 200, The Ampersand, West Tower 144 - 4th Avenue SW Calgary, Alberta T2P 3N4
Main Phone No.	(403) 205-8300 / 1 (888) 699-4853 (Mon Fri. 8 AM - 5 PM)
Transportation Emergencies Only	CANUTEC (CAN), Ph.: 1-888-CAN-UTEC (226-8832) Cell: *666, (24 hr) CHEMTREC (US), 1-800-424-9300, (24 hr)

SECTION 2. HAZARD IDENTIFICATION

Classification

Flammable gas - Category 1; Gas under pressure - Refrigerated liquefied gas; Simple asphyxiant - Category 1; Acute toxicity (Oral) - Category 4; Acute toxicity (Dermal) - Category 4; Acute toxicity (Inhalation) - Category 3; Eye irritation - Category 2; Aspiration hazard - Category 1

Label Elements



Signal Word: Danger

Hazard Statement(s):

Extremely flammable gas. Contains gas under pressure; may explode if heated. Contains refrigerated gas; may cause cryogenic burns or injury. Harmful in contact with skin. Harmful if inhaled. Causes serious eye irritation. Causes skin irritation. May displace oxygen and cause rapid suffocation.

Precautionary Statement(s):

Prevention:

Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed.





Ground and bond container and receiving equipment.

Use explosion-proof electrical, ventilating, and lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapours/spray.

Do not get in eyes, on skin, or on clothing.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF INHALED: Call a POISON CENTRE or doctor if you feel unwell. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor. Get medical advice or attention if you feel unwell. If skin irritation or rash occurs: Get medical advice or attention. Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical attention/advice.

Storage:

Store in accordance with local, regional, national and international regulations. Store in a well-ventilated place. Keep container tightly closed.

Disposal:

Dispose of contents and container in accordance with local, regional, national and international regulations.

Other Hazards

EMERGENCY OVERVIEW :

FLAMMABLE GAS. Extremely flammable. May form flammable/explosive vapour-air mixtures. Electrostatic charges may be generated during handling. Electrostatic discharges may cause fire. May be a health and fire hazard in a confined space. Very cold! Can cause cold injury.

General Hygiene Comments :

Do NOT eat, drink or store food in work areas.

Remove contaminated clothing and protective equipment before entering eating areas or leaving work area. Wash hands thoroughly after handling this product and before eating, using the washroom or leaving work area.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	%	Other Identifiers	
Liquified petroleum gas	68476-85-7	100	LPG	
Methane	74-82-8	0.0 - 0.3	Methyl hydride	
Ethane	74-84-0	0.5 - 5.0	Ethyl hydride	
Propane	74-98-6	97+	Propyl Hydride	
Isobutane	75-28-5	0.0 - 2.0	2-methylpropane	
n-Butane	106-97-8	0.0 - 0.5	Butyl hydride	
Ethyl mercaptan	75-08-1	20 - 25 ppm	Ethanethiol	



Notes

Concentrations are expressed in % volume/volume.

Product may or may not be odourized when shipped. Chemical reaction with surrounding materials can render the product non-odorized.

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

In case of oxygen deficiency: take precautions to ensure your own safety before attempting rescue (e.g. wear appropriate protective equipment). Move to fresh air. Keep at rest in a position comfortable for breathing. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by Poison Centre or doctor. If breathing has stopped, trained personnel should begin rescue breathing.

Skin Contact

Rinse with lukewarm, gently flowing water for 5 minutes. Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice or attention.

Eye Contact

Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 minutes, while holding the eyelid(s) open. Immediately call a Poison Centre or doctor and follow their advice. Seek medical attention immediately.

Ingestion

Not a likely route of exposure. Potential for aspiration. If vomiting occurs naturally, have victim lean forward to reduce the likelihood of aspiration.

Most Important Symptoms and Effects, Acute and Delayed

If inhaled:

A high concentration can displace oxygen in the air. If less oxygen is available to breathe, symptoms such as rapid breathing, rapid heart rate, clumsiness, emotional upsets and fatigue can result. As less oxygen becomes available, nausea and vomiting, collapse, convulsions, coma and death can occur. Symptoms occur more quickly with physical effort. Lack of oxygen can cause permanent damage to organs including the brain and heart.

If on skin:

Direct contact with the liquefied gas can chill or freeze the skin (frostbite). Symptoms of more severe frostbite include a burning sensation and stiffness. The skin may become waxy white or yellow. Blistering, tissue death and infection may develop in severe cases.

If in eyes:

Direct contact with the liquefied gas can freeze the eye. Permanent eye damage or blindness can result.

Immediate Medical Attention and Special Treatment

Special Instructions

Treat symptomatically. CNS asphyxiant. May cause rhinitis, bronchitis, and occasionally pulmonary edema after severe exposure. Consider oxygen therapy. Frostbite damage may occur after severe exposure. Consult a Poison Control Centre for guidance.



SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Small fire: Carbon dioxide, dry chemical powder, appropriate foam, water spray or fog.

Unsuitable Extinguishing Media

Do not use water in a stream or jet.

Specific Hazards Arising from the Product

Flammable liquid and vapour. Can ignite at room temperature. Releases vapour that can form explosive mixture with air. May displace oxygen in the air, causing rapid suffocation. Contains gas under pressure; may explode if heated. Contains refrigerated gas; may cause cryogenic burns or injury. May accumulate in hazardous amounts in low-lying areas especially inside confined spaces, resulting in a fire hazard.

Special Protective Equipment and Precautions for Fire-fighters

Stop leak/source before attempting to put out the fire. Product could form an explosive mixture and reignite. Wear full protective clothing and self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Evacuate the area immediately. Isolate the hazard area. Keep out unnecessary and unprotected personnel. Do not operate electrical equipment. Vent contaminated area thoroughly. Shut off leaks, if possible, without personal risks. Eliminate all ignition sources. Use grounded, explosion-proof equipment. Take precautionary measures against static discharge. Before entry, especially into confined areas, check atmosphere with an appropriate monitor.

Environmental Precautions

It is good practice to prevent releases into the environment.

Methods and Materials for Containment and Cleaning Up

Ventilate the area to prevent the gas from accumulating, especially in confined spaces.

Other Information

Report leaks/spills to local health, safety and environmental authorities, as required.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Only use where there is adequate ventilation. Prevent uncontrolled release of product. Eliminate heat and ignition sources such as sparks, open flames, hot surfaces and static discharge. Post "No Smoking" signs. Electrically bond and ground equipment. Ground clips must contact bare metal. Check for oxygen deficiency in work area. If used in a confined space, check for oxygen deficiency before worker entry and during work. In the event of a spill or leak, exit the area immediately. It is good practice to: avoid breathing product; avoid skin and eye contact and wash hands after handling.

Conditions for Safe Storage

Store in an area that is: cool, well-ventilated, out of direct sunlight and away from heat and ignition sources.



SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters	ACGIH TLV®		OSHA PEL		AIHA WEEL	
Chemical Name	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Methane	Not established					
Ethane	Not established					
Propane	1000 ppm					
Isobutane		1000 ppm				
n-Butane		1000 ppm	800 ppm			
Ethyl mercaptan	0.5 ppm			10 ppm		

Appropriate Engineering Controls

Do not allow product to accumulate in the air in work or storage areas, or in confined spaces. Use local exhaust and general ventilation, if necessary, to maintain air oxygen levels at a minimum of 18%. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is

Individual Protection Measures

Eye/Face Protection

Product can cause frostbite. Wear chemical safety goggles.

Skin Protection

Product can cause frostbite. Prevent all skin contact. Protect exposed skin using insulated gloves suitable for low temperatures, long sleeves, protective apron and trousers worn outside boots or over shoes.

Respiratory Protection

Not normally required if product is used as directed.

For non-routine or emergency situations: if the oxygen content of the air is below acceptable limits, wear a NIOSH approved self-contained breathing apparatus (SCBA) or supplied air respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

AppearanceColourless volatile liquefied gas.OdourSkunky (Ethyl mercaptan)Odour Threshold0.00076 ppm (Ethyl mercaptan)Melting Point/Freezing Point-189.7 °C (melting); Not available (freezing)Boiling point/Initial boiling point-42 °CFlash Point-104 °C (closed cup)Evaporation Rate> 1 (n-butyl acetate = 1)Flammability (solid, gas)Extremely flammable gas.Upper/Lower Flammability or Explosive Limit~9.5% (estimated) (Propane) (upper); > 2.1% (estimated) (Propane) (lower)Vapour Pressure~ 1303 kPa at 37.8°C (100°F)Vapour Density (air = 1)1.52Relative Density (water = 1)0.49 - 0.51 at 15 °C (59 °F)SolubilitySlightly soluble in water	Basic Physical and Chemical Properties					
Odour Threshold0.00076 ppm (Ethyl mercaptan)Melting Point/Freezing Point-189.7 °C (melting); Not available (freezing)Boiling point/Initial boiling point-42 °CFlash Point-104 °C (closed cup)Evaporation Rate> 1 (n-butyl acetate = 1)Flammability (solid, gas)Extremely flammable gas.Upper/Lower Flammability or Explosive Limit~ 9.5% (estimated) (Propane) (upper); > 2.1% (estimated) (Propane) (lower)Vapour Pressure~ 1303 kPa at 37.8°C (100°F)Vapour Density (air = 1)1.52Relative Density (water = 1)0.49 - 0.51 at 15 °C (59 °F)	Appearance	Colourless volatile liquefied gas.				
Melting Point/Freezing Point-189.7 °C (melting); Not available (freezing)Boiling point/Initial boiling point-42 °CFlash Point-104 °C (closed cup)Evaporation Rate> 1 (n-butyl acetate = 1)Flammability (solid, gas)Extremely flammable gas.Upper/Lower Flammability or Explosive Limit~ 9.5% (estimated) (Propane) (upper); > 2.1% (estimated) (Propane) (lower)Vapour Pressure~ 1303 kPa at 37.8°C (100°F)Vapour Density (air = 1)1.52Relative Density (water = 1)0.49 - 0.51 at 15 °C (59 °F)	Odour	Skunky (Ethyl mercaptan)				
Boiling point/Initial boiling point-42 °CFlash Point-104 °C (closed cup)Evaporation Rate> 1 (n-butyl acetate = 1)Flammability (solid, gas)Extremely flammable gas.Upper/Lower Flammability or Explosive Limit~ 9.5% (estimated) (Propane) (upper); > 2.1% (estimated) (Propane) (lower)Vapour Pressure~ 1303 kPa at 37.8°C (100°F)Vapour Density (air = 1)1.52Relative Density (water = 1)0.49 - 0.51 at 15 °C (59 °F)	Odour Threshold	0.00076 ppm (Ethyl mercaptan)				
Flash Point-104 °C (closed cup)Evaporation Rate> 1 (n-butyl acetate = 1)Flammability (solid, gas)Extremely flammable gas.Upper/Lower Flammability or Explosive Limit~ 9.5% (estimated) (Propane) (upper); > 2.1% (estimated) (Propane) (lower)Vapour Pressure~ 1303 kPa at 37.8°C (100°F)Vapour Density (air = 1)1.52Relative Density (water = 1)0.49 - 0.51 at 15 °C (59 °F)	Melting Point/Freezing Point	-189.7 °C (melting); Not available (freezing)				
Evaporation Rate> 1 (n-butyl acetate = 1)Flammability (solid, gas)Extremely flammable gas.Upper/Lower Flammability or Explosive Limit~ 9.5% (estimated) (Propane) (upper); > 2.1% (estimated) (Propane) (lower)Vapour Pressure~ 1303 kPa at 37.8°C (100°F)Vapour Density (air = 1)1.52Relative Density (water = 1)0.49 - 0.51 at 15 °C (59 °F)	Boiling point/Initial boiling point	-42 °C				
Flammability (solid, gas)Extremely flammable gas.Upper/Lower Flammability or Explosive Limit~ 9.5% (estimated) (Propane) (upper); > 2.1% (estimated) (Propane) (lower)Vapour Pressure~ 1303 kPa at 37.8°C (100°F)Vapour Density (air = 1)1.52Relative Density (water = 1)0.49 - 0.51 at 15 °C (59 °F)	Flash Point	-104 °C (closed cup)				
Upper/Lower Flammability or Explosive Limit~ 9.5% (estimated) (Propane) (upper); > 2.1% (estimated) (Propane) (lower)Vapour Pressure~ 1303 kPa at 37.8°C (100°F)Vapour Density (air = 1)1.52Relative Density (water = 1)0.49 - 0.51 at 15 °C (59 °F)	Evaporation Rate	> 1 (n-butyl acetate = 1)				
Explosive LimitVapour Pressure~ 1303 kPa at 37.8°C (100°F)Vapour Density (air = 1)1.52Relative Density (water = 1)0.49 - 0.51 at 15 °C (59 °F)	Flammability (solid, gas)	Extremely flammable gas.				
Vapour Density (air = 1) 1.52 Relative Density (water = 1) 0.49 - 0.51 at 15 °C (59 °F)		~ 9.5% (estimated) (Propane) (upper); > 2.1% (estimated) (Propane) (lower)				
Relative Density (water = 1) 0.49 - 0.51 at 15 °C (59 °F)	Vapour Pressure	~ 1303 kPa at 37.8°C (100°F)				
	Vapour Density (air = 1)	1.52				
Solubility Slightly soluble in water	Relative Density (water = 1)	0.49 - 0.51 at 15 °C (59 °F)				
	Solubility	Slightly soluble in water				



Partition Coefficient, n- Octanol/Water (Log Kow)	2.3
Auto-ignition Temperature	~ 470 °C
Decomposition Temperature	Not available
Viscosity	Not available (kinematic)
Other Information Physical State	Gas
Molecular Formula	C3H8
Molecular Weight	44 g/mol

SECTION 10. STABILITY AND REACTIVITY

Reactivity Not reactive.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

None expected under normal conditions of storage and use. Will not polymerize.

Conditions to Avoid

Open flames, sparks, static discharge, heat and other ignition sources. May form explosive mixture on contact with air.

Incompatible Materials

Strong oxidizing agents (e.g. perchloric acid).

Hazardous Decomposition Products

Hazardous decomposition products are not expected to form during normal storage.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation; skin contact; eye contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Methane	Not available	Not available	Not applicable
Ethane	Not available	Not available	Not available
Propane	> 800000 ppm (rat)	Not applicable	Not applicable
	(30-minute exposure)		
Isobutane	368000 mg/kg (male mouse)	> 5000 mg/kg	> 5000 mg/kg
	(4-hour exposure) (vapour)		
n-Butane	658 mg/L (rat)	Not available	
	(4-hour exposure)		Not available
Ethyl mercaptan	4420 ppm (rat)	682 mg/kg (rat)	
-	(4-hour exposure)		> 2000 mg/kg (rat)



Skin Corrosion/Irritation

Prolonged or repeated contact with the skin may cause defatting of the skin leading to redness, itching, inflammation, cracking, dermatitis (rash), and possible secondary infection. Direct contact with the liquefied gas can chill or freeze the skin (frostbite).

Serious Eye Damage/Irritation

May be irritating to eyes. Symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision. Direct contact with the liquefied gas can freeze the eye. Permanent eye damage or blindness can result.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

A high concentration can displace oxygen in the air. If less oxygen is available to breathe, symptoms such as rapid breathing, rapid heart rate, clumsiness, emotional upsets and fatigue can result. As less oxygen becomes available, nausea and vomiting, collapse, convulsions, coma and death can occur. Symptoms occur more quickly with physical effort. Lack of oxygen can cause permanent damage to organs including the brain and heart. At high concentrations: depression of the central nervous system, resulting in dizziness, light-headedness, headache, and nausea.

Skin Absorption

Not an expected route of exposure, however, exposure to cold vapour or liquid can cause severe burns.

Ingestion

Not a relevant route of exposure (gas).

Aspiration Hazard

Not known to be an aspiration hazard.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

No information was located. Not expected to be a hazard.

Respiratory and/or Skin Sensitization

Not a respiratory sensitizer. Not a skin sensitizer.

Carcinogenicity

Not known to cause cancer.

Reproductive Toxicity

Development of Offspring

No information was located. Material in general is not expected to cause harm. The material in general is not expected to produce teratogenic or embryotoxic effects. Not known to harm the unborn child.

Sexual Function and Fertility

No information was located. Material in general is not expected to cause harm. The material in general is not expected to have toxic reproductive effects.

Effects on or via Lactation

No information was located.

Germ Cell Mutagenicity

Material in general is not expected to cause harm. The material in general is not expected to produce mutagenic effects.

Interactive Effects

Not expected to be a hazard.



SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Not expected to have long term toxic effects.

Persistence and Degradability

No ingredient of this product or its degradation products is known to be highly persistent.

Bioaccumulative Potential

This product and its degradation products are not known to bioaccumulate.

Mobility in Soil

If released, this material will move rapidly through and into the environment. Contamination of groundwater could occur. If released into soil, this material will absorb and may biodegrade in anaerobic conditions. In water it may become volatile.

Other Adverse Effects

There is no information available.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Material Disposal:

Do not discharge into areas where there is a risk of forming an explosive mixture with air.

Local Legislation:

Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
Canadian TDG	1075	LIQUEFIED PETROLEUM GASES or PETROLEUM GASES, LIQUEFIED (Propane)	2.1	Not applicable
US DOT	1075	LIQUEFIED PETROLEUM GASES or PETROLEUM GASES, LIQUEFIED (Propane)	2.1	Not applicable

Product may or may not be odourized when shipped. Chemical reaction with surrounding materials can render the product nonodorized. If product is shipped non-odorized, transport info must be shown as below to be compliant;

CDN TDG: UN1075, LIQUEFIED PETROLEUM GASES or PETROELUM GASES, LIQUEFIED - NON-ODORIZED, Class 2.1 UN1075, LIQUEFIED PETROLEUM GASES or PETROELUM GASES, LIQUEFIED, Class 2.1 - NON-ODORIZED

Environmental Not applicable Hazards

Special Precautions Not applicable

Emergency Response GUIDE 115 Guide No.

Other Information Transport Class and Packing Group assigned are based on the general physical properties and composition of the material or materials tested.*Product may also be shipped domestically as; **UN1978, Propane, Class 2.1**.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations This section is not required by WHMIS.



Safety Data Sheet

PROPANE (Odorized / Non-odorized)

SECTION 16. OTHER INFORMATION					
NFPA Rating	Health - 2	Flammability - 4	Instability - 0		
SDS Prepared By Phone No.	Bureau Ver 1-800-386-	itas Canada 7247			
Date of Preparatio Date of Last Revis					
Revision Indicator	s All sections	revised form original Key	yera SDS last revision date of August 31, 2015.		
Key to Abbreviatio	OSHA = US	S Occupational Safety and	Governmental Industrial Hygienists d Health Administration s of Chemical Substances		
References CHEMINFO database. Canadian Centre for Occupational Health and Safety (CCOHS). I Pocket Guide database. National Institute for Occupational Safety and Health. Available Canadian Centre for Occupational Health and Safety (CCOHS). Registry of Toxic Effects Chemical Substances (RTECS®) database. Dassault Systèmes/BIOVIA ("BIOVIA"). Ava from Canadian Centre for Occupational Health and Safety (CCOHS).					
Disclaimer	agents of K to Bureau V material is u information underscore Although ev information or complete result of an accurate as Affiliates at information	eyera and Affiliates from a /eritas Canada. The infor used in combination with a is intended for reasonabl the potential hazards tha /ery effort is made to ensu- , it is understood that Burd eness of information and a y inaccuracy or incomplet a possible, as of the date of the address shown to ensu- related to an unusual or of	In and was developed for employees, customers and data obtained from client provided sources, and submitted ormation may not be valid or complete if the product or other products or materials, or in any process. This ole normal usage and recommended practices, and to at may be inherent to the nature of the product or material. Sure accuracy and completeness of the contained reau Veritas Canada makes no warranty as to the accuracy assumes no liability for any damage or loss suffered as theness therein. This information is considered to be as of preparation. The reader is invited to contact Keyera and neutre the information is up to date or to obtain further other use.		
	SDS repres		t Saskatchewan Facility		

Josephburg Rail Facility Rimbey Facility Edmonton Facility Hull Facility

