

Safety Data Sheet (US)

1. Identification

Product Identifier: Butane

Other Means of Identification: Butyl Hydride, Field Butane, L.P.G. (Liquefied Petroleum Gas)

Product use: Heating and cooking fuel, gasoline blending, aerosol propellant, feedstock for production of petrochemicals

Restrictions on use: Do not use for purposes other than those listed above

Manufacturer: Keyera and Affiliates






Address: Suite 600, Sunlife Plaza West
144 – 4th Avenue SW
Calgary, AB, T2P 3N4

MSDS Information: 1-780-449-7910

Emergency Contact: 1-866-377-7110 (24 hours)

2. Hazards Identification

GHS Hazards

Pictogram	Classification	Hazard Statements
	Flammable Gases – Category 1	Extremely flammable gas
	Gases Under Pressure – Liquefied Gas	Contains gas under pressure; may explode if heated.
	Specific Target Organ Toxicity, Single Exposure – Category 2	May cause damage to heart.
	Specific Target Organ Toxicity, Single Exposure – Category 3	May cause drowsiness or dizziness.
No pictogram	Simple Asphyxiant	May displace oxygen and cause rapid suffocation.
	Hazardous to the Aquatic Environment – Acute Hazard – Category 3	Harmful to aquatic life
	Hazardous to the Aquatic Environment – Long-term Hazard – Category 3	Harmful to aquatic life with long lasting effects

Other Hazards

- May cause frostbite upon sudden release of liquefied gas.

Signal Word: Danger

Precautionary Statements:

Prevention

- Keep away from heat/sparks/open flames/hot surfaces – No smoking.
- Do not breathe vapors.
- Do not eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.

Response

- Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
- Eliminate all ignition sources if safe to do so.
- If inhaled: Remove person to fresh air and keep comfortable for breathing.
- If exposed or concerned: Call a doctor/physician.
- Call a doctor/physician if you feel unwell.

Storage

- Protect from sunlight.
- Store in a well-ventilated place. Keep container tightly closed.
- Store locked up.

Disposal

- Dispose of contents/container in accordance with applicable local, provincial/state, and federal regulations.

3. Composition/Information on Ingredients

Chemical Name: Butane
Common Name/Synonyms: Butyl Hydride, Field Butane, L.P.G. (Liquefied Petroleum Gas)

Ingredient Name	Volume %	CAS No.
Methane, Ethane	Trace (0 – 0.5)	74-82-8, 74-84-0
Propane	0.2 - 5	74-98-6
iso-Butane	29 – 38	75-28-5
n-Butane	58 – 69	106-97-8
iso-Pentane	0 – 2.5	78-78-4
n-Pentane	0 – 1	109-66-0

4. First Aid Measures

Immediate Medical Attention and Special Treatment:

Treat symptomatically and supportively. Refer also to Table below.

First Aid:	
Inhalation:	Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Call a doctor/physician. Call a doctor/physician if you feel unwell.
Skin:	If cold, liquefied butane is on skin (or hair): take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: get medical advice/attention.
Eyes:	Rinse cautiously with water for several minutes. If eye irritation persists: get medical advice/attention.
Ingestion:	Not expected to be a route of exposure. See below.

Most Important Effects and Symptoms, Acute or Delayed:

Exposure Route	Health Effects	Symptoms of Exposure
Inhalation:	Butane is not classified as an asphyxiant , but can act as one by depleting the concentration of oxygen in air.	Loss of consciousness, death.
Skin:	Sudden release of liquefied gas may cause burn or frostbite.	numbness, cold or burning sensation, white, pale, greyish-yellow or red skin, blistering in severe cases.
Ingestion	In VSA (Volatile Solvent Abuse) case, when directly spraying butane into the throat the butane jet can rapidly cool to -20C by expansion, causing prolonged laryngospasm (uncontrolled muscular contraction of the laryngeal cords) and “Sudden Sniffer’s Death” from cardiac arrest.	Loss of consciousness, death.

5. Fire Fighting Measures

<p>Flammability: Yes. Butane, liquefied or in gas form, are highly flammable.</p>	<p>Hazardous Combustion Products: Carbon monoxide (CO), carbon dioxide (CO₂), and acrid smoke.</p>
<p>Explosion: Sensitive to impact: No</p>	<p>Sensitive to static discharge: Yes</p>
<p>Extinguishing Media: Small Fire: dry chemical or CO₂. Large Fire: water spray or fog.</p>	
<p>Unsuitable Extinguishing Media:</p> <ul style="list-style-type: none"> • Foam. • Water jet: Do not direct water at source of leak, especially with LPG to avoid icing. 	
<p>Special Protective Equipment for Firefighters:</p> <ul style="list-style-type: none"> • Wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face-piece. • Wear thermal protective clothing when the fire involves liquefied butane. 	
<p>Precautions for Firefighters:</p> <ul style="list-style-type: none"> • DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS THE LEAK CAN BE STOPPED. • If tank, rail car or tank truck is involved in a fire, ISOLATE and consider initial evacuation <u>in all directions</u> for 1600 meters (1 mile). • Move container from fire area if you can do it without risk. • Apply cooling water to sides of containers exposed to flames until well after fire is out. • Cool fire-exposed containers with flooding quantities of water applied from as far a distance as possible. • Stay away from ends of tanks. • Containers exposed to fire may explode or vent through pressure-relief devices. • Refer to Guide 115 of the Emergency Response Guidebook (Transport Canada/US Dept. of Transportation). 	
<p>Unusual Fire and Explosion Hazards:</p> <ul style="list-style-type: none"> • The highly flammable vapors are heavier than air and may accumulate in low areas and /or spread along ground to distant ignition sources and flash back. 	

6. Accidental Release Measures

Protective Equipment:

Gloves: Recommended: neoprene and nitrile.
 Not recommended: polyvinyl chloride PVC.

Clothing: Flame-retardant coverall e.g. Nomex, Proban. Protective apron and trousers worn over coveralls for handling liquefied butane.

Respirator: NIOSH Approved Supplied-Air Respirator or SCBA where large butane concentration is anticipated, and the exposure level is unknown or where an oxygen-deficient atmosphere may exist.

Eye: Safety glasses with side shields, safety goggles or face shields.

Large spills: wear full protective clothing and NIOSH-approved SCBA with full face-piece.

Precautions:

- Direct addition of water to liquefied gas will cause flash vaporization resulting in an explosion (either immediately or delayed) known as a "boiling liquid, expanding vapor explosion (BLEVE)".
- Do not breathe vapors.
- Do not touch spilled liquefied butane with bare skin to avoid frostbite/freeze burn.
- Liquefied butane is still highly flammable: must be kept from sparks, open flame, hot surfaces, and all sources of ignition and heat.
- The highly flammable vapors are heavier than air and may accumulate in low areas and /or spread along ground to distant ignition sources and flash back.

Emergency Procedures:

- Shut off leak/release source, if it can be done safely.
- Remove all sources of ignition.
- Isolate hazard area.
- Evacuate area of all unnecessary personnel.
 Small spill: will evaporate.
 Large spill: consider downwind evacuation of at least 800 meters (½ mile.)
 If tank, rail car or tank truck is involved in a fire, ISOLATE and consider initial evacuation in all directions for 1600 meters (1 mile).
- Keep unnecessary and unprotected personnel from entering.
- Emergency personnel must wear appropriate personal protective equipment.
- Ventilate area of leak or spill.
- If possible, turn leaking LPG containers so that gas escapes instead of liquid.

Containment and Clean-up:

- Use non-sparking tools and equipment.
- Contain and recover liquid if it can be done safely: Collect spillage with an inert material (e.g., vermiculite, dry sand, earth), and place in metal container which can be grounded.
- Do not use combustible materials, such as sawdust, as absorbent.
- If a leak or spill has not ignited, use water spray to disperse the vapors or divert vapor cloud draft. Do not direct water at spill or source of leak.
- Prevent vapors or LPG from spreading to sewers, ventilation systems, confined spaces.
- Dispose of contents/container in accordance with applicable local, provincial/state, and federal regulations.
- Refer to Guide 115 of the Emergency Response Guidebook (Transport Canada/US Dept. of Transportation).

7. Handling and Storage

Handling Precautions :

- Use only outdoors or in a well-ventilated area..
- Keep away from heat/sparks/open flames/hot surfaces – No smoking.
- Do not breathe vapors.
- Do not eat, drink or smoke when using this product.
- Use non-sparking tools and equipment.
- Wear protective gloves/ protective clothing/ eye protection/ face protection when handling liquefied butane.

Storage Precautions:

Locations

- Store in a cool, dry, well-ventilated location, away from any area of fire-hazard.
- Outside or detached storage is preferred.
- Storage and use areas should be No Smoking areas.
- Store locked-up.

Containers

- Keep container tightly closed.
- Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, sparks, flame, static electricity or other sources of ignition: they may explode and cause injury or death

Other precautions

- Separate from incompatibles like oxidizers e.g. chlorine gas and oxygen.

8. Exposure Controls / Personal Protection

EXPOSURE LIMITS

	Authority	15 MINS STEL or Ceiling	8-HOURS
Methane (CAS 74-82-8) Ethane (CAS 74-84-0)	OSHA PEL	-	-
	ACGIH TLV	Limits withdrawn. Instead, refer to "Minimal Oxygen Content" Appendix F of ACGIH*	
	NIOSH	-	-
Propane (CAS 74-98-6)	OSHA PEL	-	1000 ppm (1800 mg/m ³)
	ACGIH TLV	Identified as an asphyxiant	
	NIOSH	-	1000 ppm (1800 mg/m ³)
Butane (all isomers)	OSHA PEL	-	-
	ACGIH TLV	1000 ppm (2370 mg/m ³)	-
	NIOSH	-	800 ppm (1900 mg/m ³)
Pentane (all isomers)	OSHA PEL	-	1000 ppm (2950 mg/m ³)
	ACGIH TLV	-	1000 ppm (2950 mg/m ³)
	NIOSH (for n-pentane only)	610 ppm (1800 mg/m ³) ceiling	120 ppm (350 mg/m ³)
	Alberta, Ontario, BC		600 ppm (1770 mg/m ³) 600 ppm
L.P.G. (Liquefied Petroleum Gas) (CAS 68476-85-7)	OSHA/NIOSH: IDLH, 2100 ppm Because L.P.G. may cause asphyxia at concentrations well above the lower explosive limit (LEL), the revised IDLH for L.P.G. is 2,000 ppm based strictly on safety considerations (i.e., being about 10% of the LELs of 1.9% for butane and 2.1% for propane).		



ENGINEERING CONTROLS

- Ventilate area where product is used, stored and/or handled to maintain airborne concentrations below the LEL and OEL, especially in confined spaces.
- Exhaust/ventilate to the outside.
- Ventilation equipment must be explosion proof.
- Ventilation system should be grounded and separate from other exhaust ventilation systems. Adequate make-up air must be provided.



PERSONAL PROTECTIVE EQUIPMENT

- Gloves:** Recommended: neoprene and nitrile;
Not recommended: polyvinyl chloride PVC..
- Clothing:** Flame-retardant coverall e.g. Nomex, Proban. Protective apron and trousers worn over coveralls for handling liquefied butane.
- Respirator:** NIOSH Approved Supplied-Air Respirator or SCBA where large butane concentration is anticipated, and the exposure level is unknown or where an oxygen-deficient atmosphere may exist.
- Eye:** Safety glasses with side shields, safety goggles or face shields.

9. Physical and Chemical Properties

Chemical Formula: C ₄ H ₁₀	Molecular Weight: 58.12 g/mole	Chemical Family: Hydrocarbon
Appearance: Colorless gas	Odor: Slight gasoline odor	Odor Threshold: Unknown
pH: Not applicable	Melting/Freezing Point: -140 to -134°C (-220 to -209°F)	Boiling Point: -1 to 1°C (30-34°F)
Flash Point: <-60°C (-76°F) Closed Cup	Flammability: Yes	Evaporation Rate: >1 (Butyl Acetate = 1)
Upper-Lower Explosive Limit: 1.6% (LEL), 8.4% (UEL)	Vapor Pressure: ~ 300-340 kPa	Vapor Density: ~2 (air = 1)
Specific Gravity: Liquid: 0.574-0.578	Soluble in water (@20°C): Slightly soluble ~50-60 mg/L	Percent Volatile: 100 by volume
Partition Coefficient n-octanol/water: Log Kow = 2.89-2.76	Auto-Ignition Temperature: 288°C (550°F)	Decomposition Temp.: Not available
Viscosity: Not available	Henry's Law Constant: Not available	Isobaric Heat Capacity: Not available

10. Stability and Reactivity

Reactivity: Avoid incompatible materials: may react violently with oxidizers.
Chemical Stability: Stable under normal temperatures and pressures.
Possibility of Hazardous Reactions: Polymerization has not been reported to occur under normal temperature and pressure conditions.
Conditions to Avoid: Extreme temperatures and incompatible materials.
Incompatible Materials: <ul style="list-style-type: none"> • <u>Oxidizers</u>: may react violently with oxidizers including chlorine gas and oxygen.
Hazardous Decomposition Products: <ul style="list-style-type: none"> • No decomposition if stored and applied as directed. • Combustion forms carbon monoxide, carbon dioxide, irritating and toxic fumes/gases.

11. Toxicological Information

Exposure Route	Acute Health Effects	Symptoms of Exposure
Inhalation:	Effects on the Central Nervous system (CNS) at >1% (10,000ppm) may range from mild (respiratory depression) to severe (asphyxiation).	may range from rapid breathing, dizziness to respiratory arrest, loss of consciousness (narcosis) and death in extreme cases.
Skin:	In gas form: no known effects.	-
	In liquid form: burn or frostbite.	numbness, cold or burning sensation, white, pale, greyish-yellow or red skin, blistering in severe cases.
Eye:	In gas form: no known effects.	-
	In liquid form: burn or frostbite.	numbness, cold or burning sensation, blistering to blindness in severe cases.
Ingestion:	Not expected to be a route of exposure. In VSA (Volatile Solvent Abuse) case, when directly spraying butane into the throat the butane jet can rapidly cool to -20C by expansion, causing prolonged laryngospasm (uncontrolled muscular contraction of the laryngeal cords) and "Sudden Sniffer's Death" from cardiac arrest.	

Chronic Exposure:
Inhalation:

Repeated or prolonged exposure may cause damage to the Central Nervous System (CNS), the nervous and the heart system.

Skin:

Not known to be a skin-sensitizer. Repeated and prolonged contact may cause dry, red, cracked skin (dermatitis).

Medical Conditions Aggravated by Exposure:

Possibly asthma.

Sensitization: No	Reproductive Toxicology: No	Teratogenicity: No	Mutagenicity: No
Carcinogenicity: Not listed by ACGIH, IARC, NIOSH, NTP, or OSHA.	Irritancy: No.	Target Organs: Central Nervous System (CNS).	

Lethality Tests:

Chemical Name	CAS No.	LC50 or LD50
Ethane	74-84-0	Rat, inhalation: 658 mg/L 4 hrs.
Propane	74-98-6	Rat, inhalation: >800000ppm, 15-mins (oxygen was also added to maintain a level of ~20vol%)
		Rat, inhalation: 658 mg/L 4hrs.
n-Butane	106-97-8	Rat, inhalation: 658 mg/L 4hrs.
Iso-butane	72-28-5	Rat, inhalation: 658 mg/L 4hrs.
n-Pentane	109-66-0	Rat, inhalation: 364 mg/L 4 hrs. Mouse, oral: 5000 mg/kg

12. Ecological Information

<p>Persistence & Degradability: Not expected to persist in the environment. Both butanes are expected to undergo biodegradation in soil.</p>	<p>Bioaccumulative Potential: Not expected to bioaccumulate.</p>
<p>Mobility: When released to soil, n-butane is expected to have a low mobility (partition coefficient organic carbon to water, $K_{oc} = \sim 900$), while isobutane will have a high mobility ($K_{oc} \sim 35$)</p>	<p>Other Adverse Effects: See below.</p>

Terrestrial Fate:

- For both butanes, volatilization from soil surfaces is expected to be an important fate process, based upon an estimated Henry's Law constant of 0.95 – 1.19 atm-cu m/mole.
- Photolysis and hydrolysis are not expected to be important in soil.
- Groundwater contamination is not expected.

Aquatic Fate:

- Butane is only slightly soluble in water. Spills will spread on the water surface and the majority will evaporate. Estimated volatilization half-lives for a model river and model lake are 2 hours and 3 days, respectively.
- Hydrolysis is not expected to be an important environmental fate process since both n-butane and isobutane lacks functional groups that hydrolyze under environmental conditions.

Atmospheric Fate:

- If released to air, butanes (n-butane and isobutane) will exist solely as gas in the atmosphere.
- Butanes are not expected to be susceptible to direct photolysis by sunlight, but will be degraded in the atmosphere by reacting with hydroxyl radicals; the half-life for this reaction in air is estimated to be 6-7 days.
- Butanes also has the potential to partake in photochemical reactions to produce ozone pollutant.

Eco Toxicity Tests:

Chemical Name	Species	Test Method	LC50/ EC50/
Iso-Pentane (CAS 78-78-4)	Daphnia magna (water flea)	Static test; 48 hours	EC50 = 2.3 mg/L
n-Pentane (CAS 109-66-0)	Daphnia magna (water flea)	Static test; 48 hours	LC50 = 9.74 mg/L
	Oncorhynchus mykiss (rainbow trout)	Semi-static test; 96 hours	LC50 = 9.87 mg/L
	Pimephales promelas (fathead minnow)	Semi-static test; 96 hours	LC50 = 11.59 mg/L
	Lepomis macrochirus (bluegill sunfish)	Semi-static test; 96 hours	LC50 = 9.99 mg/L

13. Disposal Considerations

Waste Disposal:

- Dispose of waste material at an approved waste treatment/disposal facility in accordance with applicable local, provincial, and federal regulations.
- Excess/waste butane can be disposed by incineration in a waste gas incinerator or flare.
- Butane can also be reused as fuel for boilers and heaters.

14. Transport Information

DOT (U.S.) CLASSIFICATION

PROPER SHIPPING NAME: Liquefied Petroleum Gas
CLASS: 2.1 **UN NUMBER:** UN1075
PACKING GROUP: None **LABEL/PLACARD:**



PROPER SHIPPING NAME: Liquefied Gas, Flammable, N.O.S. (n-Butane/iso-Butane mixture)
CLASS: 2.1 **UN NUMBER:** UN3161
PACKING GROUP: None **LABEL/PLACARD:**



MARINE POLLUTANT: No

15. Regulatory Information

UNITED STATES

Regulatory List	Chemical
TSCA: Toxic Substance Control Act Inventory List	All the components are listed
CCA: Clean Air Act – Accidental Release Prevention – Flammable Substances (1000 lb. threshold quantity)	All the components are listed

16. Other Information

NFPA Hazard Rating:

Health 1, Flammability 4, Instability 0



Prepared for:

Keyera Health and Safety

Issue Date/ Revision No:

November 30, 2014/ Revision #2

Revisions:

- Original:
- 1st revision:
- 2nd revision:

Dates:

April 25, 2013
 January 31, 2014
 November 30, 2014

Main Changes

reformat
 GHS format

Disclaimer of Expressed and Implied Warranties

The information presented in the Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. However, neither Keyera nor its affiliates assumes any liability whatsoever for the accuracy or completeness of the information contained herein. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.

~ End of Safety Data Sheet ~